



**DISCLAIMER: UNIVERSALPEGASUS INTERNATIONAL MAKES NO WARRANTY (EXPRESSED, IMPLIED OR OTHERWISE) THAT THE INFORMATION CONTAINED HEREIN IS ACCURATE OR COMPLETE AS TO ANY AND ALL SUBSURFACE CONDITIONS AND CONFORMATION. ANY RELIANCE CONTRACTOR PLACES ON THE INFORMATION CONTAINED HEREIN AS TO SUCH CONDITIONS, IS DONE SO AT ITS OWN RISK AND EXPENSE. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE STATE "ONE CALL" SYSTEM PRIOR TO ANY EXCAVATION.**

SURVEY DATA		STATIONING	
MATCHLINE 294+00	294+00	MATCHLINE 340+00	340+00
294+81		338+62	
299+26		338+47	
299+46		328+77	
302+25		338+61	
302+31		338+61	
302+37		338+79	
307+76		338+79	
310+65		338+61	
312+15		338+61	
315+84		338+61	
316+99		338+61	
317+74		338+61	
328+46		338+61	
328+47		338+61	
328+77		338+61	
338+62		338+61	

BILL OF MATERIALS				MISCELLANEOUS MATERIALS				TYPICAL DRAWINGS				GENERAL INFORMATION				REVISIONS				APPROVALS					
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.	1	DESCRIPTION	DATE	REV BY	CHK BY	APP BY	DRAWN BY:	MB	CONSTRUCTION PERMIT NO.							
1	3769	FT	36" O.D. x 0.520" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	115	EA	SET ON WEIGHTS	21040-510-TYP-20001	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.	2	NO.					CHECKED BY:	MJ	MAINTENANCE OPERATION REGION							
6	831	FT	36" O.D. x 0.750" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	5	EA	PIPELINE MARKERS	21040-510-TYP-20002	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.	3	1	IFC (UPDATE ENV., RE-ROUTES, FOOT-PRINT)	2016-04-08	MB	MJ	RG	PROJECT MANAGER	RG	MIN. TEST PRESSURE	1816	PSI				
FITTINGS SUMMARY				CONTINUOUS CONCRETE COATING				SPECIAL NOTES				ENVIRONMENTAL				COMPANY									
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	DESCRIPTION	21040-510-TYP-20028	TYPICAL OPEN CUT / BORE	4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.	4	ENVIRONMENTAL	LAND	APPROVAL	COMPANY	0	ISSUED FOR CONSTRUCTION	2015-12-15	MB	MJ	RG	PROJECT DEF. NO.		DESIGN PRESSURE	1440	PSI
1	EA		90" 3R HORIZONTAL FITTING	1153	FT	7" OF CONTINUOUS CONCRETE COATING (140 PCF DENSITY CONCRETE)	21040-510-TYP-20012	CONTINUOUS CONCRETE COATING STANDARD FOR 36" / 30" PIPELINE	5. ADDITIONAL WARNING SIGNS MAY BE REQUIRED AS DICTATED BY CONSTRUCTION CONTRACT.	5	APPROVAL		COMPANY		UNIVERSAL PEGASUS INTERNATIONAL		FLORIDA SOUTHEAST CONNECTION		FLORIDA SOUTHEAST CONNECTION PROJECT		STA: 294+00 TO 340+00	DISCIPLINE: 03			
PIPE ASSEMBLIES				PIPE COATING DATA				LEGEND				SCALE: 1" = 200 FT				FLORIDA SOUTHEAST CONNECTION ALIGNMENT SHEET POLK COUNTY, FLORIDA									
DESCRIPTION				PIPE COATING: 14 MIL MINIMUM FBE AND 24 MIL MINIMUM ARO GIRTH WELD COATING: 2 PART EPOXY INTERNAL COATING (YES/NO): NO				LEGEND				1 INCH = 200 FT				SCALE: 1" = 200'									
DESCRIPTION				INTERNAL COATING (YES/NO): NO				LEGEND				1 INCH = 200 FT				SCALE: 1" = 200'									