



SURVEY DATA		STATIONING	
MATCHLINE 1550+00	MATCHLINE 1575+00	MATCHLINE 1550+00	MATCHLINE 1575+00

ENGINEERING DATA		MATERIAL	
REFERENCE DRAWING	21040-440-PMW-00029	740'	519'
CLASS LOCATION	Class II	1556+02	1557+40
MINIMUM DEPTH OF COVER	3'	1558+61	1559+16
AC MITIGATION / CATHODIC PROTECTION	SEE REF DWG	1559+28	1559+81

ENVIRONMENTAL DATA		STATIONS	
WATERBODY/WETLAND CROSSINGS	THIS BAND NOT UTILIZED	MATCHLINE 1550+00	MATCHLINE 1575+00
WATERBODY/WETLAND LENGTH	THIS BAND NOT UTILIZED		
THREATENED AND ENDANGERED SPECIES	Potential Sand Skink Habitat		

BILL OF MATERIALS				MISCELLANEOUS MATERIALS				TYPICAL DRAWINGS		GENERAL INFORMATION		LEGEND		REVISIONS				APPROVALS				
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.	1. INDUCTION BEND QUANTITIES ALONG WITH THEIR DESCRIPTIONS ARE LOCATED ON DRAWING 21040-505-FBW-00001.	HD PIPE	PIPELINE ROUTE	NO.	DESCRIPTION	DATE	REV BY	CHK BY	APP BY	DRAWN BY:	MB	CONSTRUCTION PERMIT NO.	
4	120	FT	36" O.D. x 0.750" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE & 24-30 MILS ARO	0	EA	SET ON WEIGHTS	21040-510-TYP-20001	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.	2. 3 - SEE ARK DRAWING PACKAGE FOR ANODE BED DEEP WELL.	BORE PIPE	FENCE	1									
5	740	FT	36" O.D. x 0.625" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	2	EA	PIPELINE MARKERS	21040-510-TYP-20002	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.		3R RAD FIT	POWER LINE	2									
6	1640	FT	36" O.D. x 0.750" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	3	EA	WARNING SIGNS	21040-510-TYP-20028	TYPICAL OPEN CUT / BORE	4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.		INDUCTION BEND	TELEPHONE LINE	3									
				0	EA	CP TEST STATION TYPE 1	21040-510-TYP-20029	CONT. CONC. COAT.	5. ADDITIONAL WARNING SIGNS MAY BE REQUIRED AS DICTATED BY CONSTRUCTION CONTRACT.		TRANSITION PIPE	WATERLINE	4									
				0	EA	CP TEST STATION TYPE 2		SET ON WEIGHTS	6. MAP PROJECTION: NAD 1983 HARN STATE PLANE FLORIDA EAST FIPS 9501 FEET. VERTICAL DATUM: NAVD 88.		SEWER LINE	GENERAL SURVEY	5									
				0	EA	AERIAL MARKERS	21040-510-TYP-20112	CONTINUOUS CONCRETE COATING STANDARD FOR 36" / 30" PIPELINE			BURIED CABLE	UTILITY LINE	6									
				0	EA	ANODE BED DEEP WELL		TYPICAL SADDLE BAG WEIGHTS			UTILITY LINE	GENERAL SURVEY	7									
				0	EA			WARNING SIGN DETAIL			ROW PARCEL	PLSS SECTION LINE	8									
				0	EA			AERIAL MARKER INSTALLATION DETAIL			PRIVATE ACCESS / SHOULDER ROAD	ROW PARCEL	PLSS SECTION LINE	9								
				0	EA			AERIAL MARKER DETAIL			PIPELINE MARKER	TRAP	WATER WELL	10								
				0	EA			TYPICAL PIPELINE MARKER ASSEMBLY			PIPELINE MILEPOST	ANODE BED DEEP WELL	HD ENTRY / EXT	11								
				0	EA			PIPELINE MARKER "WARNING" DECAL			ANODE BED DEEP WELL	HD ENTRY / EXT	12									