



DISCLAIMER: UNIVERSALPEGASUS INTERNATIONAL MAKES NO WARRANTY (EXPRESSED, IMPLIED OR OTHERWISE) THAT THE INFORMATION CONTAINED HEREIN IS ACCURATE OR COMPLETE AS TO ANY AND ALL SUBSURFACE CONDITIONS AND CONFORMATION. ANY RELIANCE CONTRACTOR PLACES ON THE INFORMATION CONTAINED HEREIN AS TO SUCH CONDITIONS, IS DONE SO AT ITS OWN RISK AND EXPENSE. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE STATE "ONE CALL" SYSTEM PRIOR TO ANY EXCAVATION.

SURVEY DATA		STATIONING
MATCHLINE 3400+00	3408+36 FENCE CORNER LT 12' 3408+38 FENCE CORNER RT 12' 3408+50 UNNAMED RD 3408+63 FENCE CORNER 3408+67 FENCE CORNER 3408+26 FENCE CORNER LT 13'	MATCHLINE 3450+00

ENGINEERING DATA		MATERIAL
MATCHLINE 3400+00	3403+96 3408+40 3413+96 3422+06 3422+61 3428+46 3431+54 3436+49 3438+49 3443+39 3443+85 3448+99 3449+99	MATCHLINE 3450+00

ENVIRONMENTAL DATA		STATIONS
MATCHLINE 3400+00	3407+90 3408+30 3422+62 3423+15 3423+56 3428+46 3436+23 3438+43 3439+99 3444+20 3448+99 3449+99	MATCHLINE 3450+00

BILL OF MATERIALS		MISCELLANEOUS MATERIALS	TYPICAL DRAWINGS	GENERAL INFORMATION								
ITEM NO.	QTY	UOM	REQ#	MATERIAL NUMBER	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.				
1	5000	FT			36" O.D. x 0.520" W.T., API SL, X70, PSL2, DSAW, 14-16 MILS FBE	21040-510-TYP-20001	SET ON WEIGHTS	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.				
2	EA				PIPELINE MARKERS	21040-510-TYP-20002	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.				
4	EA				WARNING SIGNS	21040-510-TYP-20028	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.				
1	EA				CP TEST STATION TYPE 1	21040-510-TYP-20112	CONTINUOUS CONCRETE COATING STANDARD FOR 36" / 30" PIPELINE	5. ADDITIONAL WARNING SIGNS MAY BE REQUIRED AS DICTATED BY CONSTRUCTION CONTRACT.				
0	EA				CP TEST STATION TYPE 2	21040-510-TYP-20113	TYPICAL SADDLE BAG WEIGHTS	6. MAP PROJECTION: NAD 1983 HARN STATE PLANE FLORIDA EAST FIPS 0901 FEET. VERTICAL DATUM: NAVD 88.				
1	EA				AERIAL MARKERS	21040-510-TYP-20114	WARNING SIGN DETAIL					
0	EA				ANODE BED DEEP WELL	21040-510-TYP-20115	AERIAL MARKER INSTALLATION DETAIL					
FITTINGS SUMMARY		CONTINUOUS CONCRETE COATING		PIPE COATING DATA		SPECIAL NOTES						
ITEM NO.	QTY	UOM	REQ#	MATERIAL NUMBER	DESCRIPTION	ITEM NO.	QTY	UOM	REQ#	MATERIAL NUMBER	DESCRIPTION	1. INDUCTION BEND QUANTITIES ALONG WITH THEIR DESCRIPTIONS ARE LOCATED ON DRAWING 21040-505-FBW-00001.
PIPE ASSEMBLIES		GIRTH WELD COATING: 2 PART EPOXY		INTERNAL COATING (YES/NO): NO		2. 3 - SEE ARK DRAWING PACKAGE FOR ANODE BED DEEP WELL.						

LEGEND		REVISIONS		APPROVALS						
HDD PIPE	PIPELINE ROUTE	NO.	DESCRIPTION	DATE	REV BY	CHK BY	APP BY	DRAWN BY:	MB	CONSTRUCTION PERMIT NO.
BORE PIPE	FENCE							CHECKED BY:	MJ	MAINTENANCE OPERATION REGION
LINE PIPE	POWER LINE	1	IFC (UPDATE ENV., RE-ROUTES, FOOT-PRINT)	2016-04-08	MB	MJ	RG	PROJECT MANAGER	RG	MIN. TEST PRESSURE 1816 PSI
3R RAD FIT	TELEPHONE LINE	0	ISSUED FOR CONSTRUCTION	2015-12-15	MB	MJ	RG	PROJECT DEF. NO.		DESIGN PRESSURE 1440 PSI
INDUCTION BEND	WATERLINE	APPROVAL		COMPANY						
TRANSITION PIPE	SEWER LINE	ENVIRONMENTAL		LAND		STA: 3400+00 TO 3450+00 DISCIPLINE: 03		FLORIDA SOUTHEAST CONNECTION ALIGNMENT SHEET OSCEOLA COUNTY, FLORIDA		
CONT. CONC. COAT.	BURIED CABLE	SCALE: 1" = 200'		21040-510-ALS-00073		REV. 1		SHEET 73		
BY MOV. BY CV	UTILITY LINE	1 INCH = 200 FT								
PIPELINE MARKER	GENERAL SURVEY									
ANODE BED DEEP WELL	FOREIGN PIPELINE									
	RAILROAD									
	HIGHWAY / ROAD									
	PRIVATE ACCESS / SHOOLY ROAD									
	COUNTY BOUNDARY									
	PLSS SECTION LINE									
	WATER WELL									
	HDD ENTRY / EXIT									