



SURVEY DATA	STATIONING	DESCRIPTION
MATCHLINE 3600+00	3600+00	3600+48 STANDING INFORMATION PIPE RT 25'
MATCHLINE 3600+00	3611+99	
MATCHLINE 3600+00	3617+94	
MATCHLINE 3600+00	3627+94	3630+72 POWER POLE LT RT 2'
MATCHLINE 3600+00	3627+94	3630+75 GUY ANCHOR RT 2'
MATCHLINE 3600+00	3627+94	
MATCHLINE 3600+00	3643+68	3643+68 MONUMENT LT 20'
MATCHLINE 3650+00	3650+00	

ENGINEERING DATA	MATERIAL	DESCRIPTION
MATCHLINE 3600+00	3611+99	
MATCHLINE 3600+00	3617+94	
MATCHLINE 3600+00	3627+94	14-9K# SBW 10.5 CC
MATCHLINE 3600+00	3627+94	
MATCHLINE 3600+00	3643+68	
MATCHLINE 3650+00	3650+00	

ENVIRONMENTAL DATA	STATIONS	DESCRIPTION
MATCHLINE 3600+00	3611+99	
MATCHLINE 3600+00	3617+94	
MATCHLINE 3600+00	3627+94	
MATCHLINE 3600+00	3627+94	
MATCHLINE 3600+00	3643+68	
MATCHLINE 3650+00	3650+00	

BILL OF MATERIALS				MISCELLANEOUS MATERIALS				TYPICAL DRAWINGS		GENERAL INFORMATION		REVISIONS				APPROVALS					
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	REQ#	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.		NO.		DESCRIPTION	DATE	REV BY	CHK BY	APP BY	DRAWN BY:	MB	CONSTRUCTION PERMIT NO.
1	5000	FT	36" O.D. x 0.520" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	14	EA		SET ON WEIGHTS	21040-510-TYP-20001	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.		1		IFC (UPDATE ENV., RE-ROUTES, FOOT-PRINT)	2016-04-08	MB	MJ	RG	PROJECT MANAGER	RG	MIN. TEST PRESSURE 1816 PSI
				5	EA		PIPELINE MARKERS			3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.		0		ISSUED FOR CONSTRUCTION	2015-12-15	MB	MJ	RG	PROJECT DEF. NO.		DESIGN PRESSURE 1440 PSI
				0	EA		WARNING SIGNS	21040-510-TYP-20002	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.		1		APPROVAL		COMPANY					
				1	EA		CP TEST STATION TYPE 1	21040-510-TYP-20028	TYPICAL OPEN CUT / BORE	5. ADDITIONAL WARNING SIGNS MAY BE REQUIRED AS DICTATED BY CONSTRUCTION CONTRACT.		0		ENVIRONMENTAL						STA: 3600+00 TO 3650+00    DISCIPLINE: 03	
				0	EA		CP TEST STATION TYPE 2	21040-510-TYP-20112	CONTINUOUS CONCRETE COATING STANDARD FOR 36" / 30" PIPELINE	6. MAP PROJECTION: NAD 1983 HARN STATE PLANE FLORIDA EAST FIPS 0901 FEET. VERTICAL DATUM: NAVD 88.		0		LAND						FLORIDA SOUTHEAST CONNECTION PROJECT <b>FLORIDA SOUTHEAST CONNECTION ALIGNMENT SHEET</b> OSCEOLA COUNTY, FLORIDA	
				0	EA		AERIAL MARKERS	21040-510-TYP-20113	TYPICAL SADDLE BAG WEIGHTS	SPECIAL NOTES		0						SCALE: 1" = 200' 21040-510-ALS-00077		REV. 1	
				0	EA		ANODE BED DEEP WELL	21040-510-TYP-20114	WARNING SIGN DETAIL	1. INDUCTION BEND QUANTITIES ALONG WITH THEIR DESCRIPTIONS ARE LOCATED ON DRAWING 21040-505-FBW-00001.		0									
FITTINGS SUMMARY				CONTINUOUS CONCRETE COATING				PIPE COATING DATA													
ITEM NO.	QTY	UOM	REQ#	MATERIAL NUMBER	DESCRIPTION	QTY	UOM	REQ#	DESCRIPTION	PIPE COATING: 14 MIL MINIMUM FBE AND 24 MIL MINIMUM ARO											
										GIRTH WELD COATING: 2 PART EPOXY											
										INTERNAL COATING (YES/NO): NO											