



DISCLAIMER: UNIVERSALPEGASUS INTERNATIONAL MAKES NO WARRANTY (EXPRESSED, IMPLIED OR OTHERWISE) THAT THE INFORMATION CONTAINED HEREIN IS ACCURATE OR COMPLETE AS TO ANY AND ALL SUBSURFACE CONDITIONS AND CONFORMATION. ANY RELIANCE CONTRACTOR PLACES ON THE INFORMATION CONTAINED HEREIN AS TO SUCH CONDITIONS, IS DONE SO AT ITS OWN RISK AND EXPENSE. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE STATE "ONE CALL" SYSTEM PRIOR TO ANY EXCAVATION.

SURVEY DATA		STATIONING	
MATCHLINE 5300+00	5300+00	MATCHLINE 5300+00	5300+00
MATCHLINE 5350+00	5350+00	MATCHLINE 5350+00	5350+00

ENGINEERING DATA		MATERIAL	
MATCHLINE 5300+00	5300+00	MATCHLINE 5300+00	5300+00
MATCHLINE 5350+00	5350+00	MATCHLINE 5350+00	5350+00

ENVIRONMENTAL DATA		STATIONS	
MATCHLINE 5300+00	5300+00	MATCHLINE 5300+00	5300+00
MATCHLINE 5350+00	5350+00	MATCHLINE 5350+00	5350+00

BILL OF MATERIALS				MISCELLANEOUS MATERIALS				TYPICAL DRAWINGS		GENERAL INFORMATION		LEGEND		REVISIONS		APPROVALS			
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	REQ#	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.	HDD PIPE	PIPELINE ROUTE	NO.	DESCRIPTION	DATE	REV BY	CHK BY	APP BY	
9	120	FT	30" O.D. x 0.429" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	44	EA		SET ON WEIGHTS	21040-510-TYP-20001	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.	BORE PIPE	FENCE	1	IFC (UPDATE ENV., RE-ROUTES, FOOT-PRINT)	2016-04-08	MB	MJ	RG	
			30" O.D. x 0.514" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE & 24-30 MILS ARO	6	EA		PIPELINE MARKERS	21040-510-TYP-20002	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.	3R RAD FIT	POWER LINE	2	ISSUED FOR CONSTRUCTION	2015-12-15	MB	MJ	RG	
FITTINGS SUMMARY				CONTINUOUS CONCRETE COATING				TYPICAL OPEN CUT / BORE		4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.	INDUCTION BEND	TELEPHONE LINE	APPROVAL		COMPANY		UNIVERSALPEGASUS INTERNATIONAL		
PIPE ASSEMBLIES				PIPE COATING DATA				AERIAL MARKER INSTALLATION DETAIL		5. ADDITIONAL WARNING SIGNS MAY BE REQUIRED AS DICTATED BY CONSTRUCTION CONTRACT.	TRANSITION PIPE	WATERLINE	ENVIRONMENTAL		FLORIDA SOUTHEAST CONNECTION		FLORIDA SOUTHEAST CONNECTION PROJECT		
GIRTH WELD COATING: 2 PART EPOXY				INTERNAL COATING (YES/NO): NO				AERIAL MARKER DETAIL		6. MAP PROJECTION: NAD 1983 HARN STATE PLANE FLORIDA EAST FIPS 0901 FEET. VERTICAL DATUM: NAVD 88.	CONT. CONC. COAT.	SEWER LINE	LAND		FLORIDA SOUTHEAST CONNECTION ALIGNMENT SHEET		OKEECHOBEE COUNTY, FLORIDA		
INTERNAL COATING (YES/NO): NO								WARNING SIGN DETAIL		SPECIAL NOTES		BURIED CABLE	GENERAL SURVEY	SCALE: 1" = 200'		21040-510-ALS-00112		REV. 1	
								CP TEST STATION TYPE 1		1. INDUCTION BEND QUANTITIES ALONG WITH THEIR DESCRIPTIONS ARE LOCATED ON DRAWING 21040-505-FBW-00001.		UTILITY LINE	COUNTY BOUNDARY	1 INCH = 200 FT					
								CP TEST STATION TYPE 2		2. SEE ARK DRAWING PACKAGE FOR ANODE BED DEEP WELL.		BY MOV. BY & CV	ROW PARCEL						
								AERIAL MARKERS				PLSS SECTION LINE	TRAP						
								ANODE BED DEEP WELL				WATER WELL	HDD ENTRY / EXIT						