



**DISCLAIMER:** UNIVERSALPEGASUS INTERNATIONAL MAKES NO WARRANTY (EXPRESSED, IMPLIED OR OTHERWISE) THAT THE INFORMATION CONTAINED HEREIN IS ACCURATE OR COMPLETE AS TO ANY AND ALL SUBSURFACE CONDITIONS AND CONFORMATION. ANY RELIANCE CONTRACTOR PLACES ON THE INFORMATION CONTAINED HEREIN AS TO SUCH CONDITIONS, IS DONE SO AT ITS OWN RISK AND EXPENSE. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE STATE "ONE CALL" SYSTEM PRIOR TO ANY EXCAVATION.

SURVEY DATA		STATIONING	
MATCHLINE 6200+00		MATCHLINE 6250+00	
6205+48 TOP OF BANK 6205+48 TOP OF BANK 6206+02 CLAR. 1301 6206+02 UNNAMED RD 6206+20 FENCE POST LT 6206+20 FENCE POST LT		6209+48 TOP OF BANK 6209+48 TOP OF BANK 6209+78 TOP OF BANK 6210+87 FENCE POST LT 6210+90 FENCE	
MATCHLINE 6200+00		MATCHLINE 6250+00	
6202+00 6204+91 6206+29 6209+00 6210+61 6210+90 6214+63 6217+05 6220+00 6230+00 6231+87 6234+91 6234+96 6237+25 6237+31 6238+05 6241+52 6242+26 6242+30 6248+38		13-7K# SBW 11.5 CC 15-7K# SBW 11.5 CC 22-7K# SBW 11.5 CC 3187' 304' 240' 13 CC 1269'	
ENGINEERING DATA		MATERIAL	
REFERENCE DRAWING			
CLASS LOCATION		Class I	
MINIMUM DEPTH OF COVER		3'	
AC MITIGATION / CATHODIC PROTECTION			
WATERBODY/WETLAND CROSSINGS		W-602, W-604, W-603, W-80A	
WATERBODY/WETLAND LENGTH		29', 55', 135', 21'	
ENVIRONMENTAL DATA		STATIONS	
PERMANENT EROSION CONTROL		EROSION CONTROL CODE	
SLOPE BREAKER CODE		THIS BAND NOT UTILIZED	
TOPSOIL SAVAGE		THIS BAND NOT UTILIZED	
THREATENED AND ENDANGERED SPECIES		THIS BAND NOT UTILIZED	
TIMING CONSTRAINT		THIS BAND NOT UTILIZED	
CONSTRAINT 2		THIS BAND NOT UTILIZED	
CONSTRAINT 3		THIS BAND NOT UTILIZED	
CONSTRAINT 4		THIS BAND NOT UTILIZED	

BILL OF MATERIALS				MISCELLANEOUS MATERIALS				TYPICAL DRAWINGS		GENERAL INFORMATION		LEGEND		REVISIONS				APPROVALS				
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	REQ'N NUMBER	MATERIAL NUMBER	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.	PIPELINE ROUTE	PERMANENT ROW	NO.	DESCRIPTION	DATE	REV BY	CHK BY	APP BY	DRAWN BY:	MB	CONSTRUCTION PERMIT NO.
10	240	FT	30" O.D. x 0.617" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	57	EA			SET ON WEIGHTS	21040-510-TYP-20001	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.	PIPELINE ROUTE	PERMANENT ROW	1	IFC (UPDATE ENV., RE-ROUTES, FOOT-PRINT)	2016-04-08	MB	MJ	RG	PROJECT MANAGER	RG	MIN. TEST PRESSURE 1816 PSI
12	1573	FT	30" O.D. x 0.617" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	4	EA			WARNING SIGNS	21040-510-TYP-20002	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.	PIPELINE ROUTE	PERMANENT ROW	0	ISSUED FOR CONSTRUCTION	2015-12-15	MB	MJ	RG	PROJECT DEF. NO.		DESIGN PRESSURE 1440 PSI
FITTINGS SUMMARY				CONTINUOUS CONCRETE COATING				TYPICAL OPEN CUT / BORE		SPECIAL NOTES		LEGEND		APPROVALS								
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	REQ'N NUMBER	MATERIAL NUMBER	DESCRIPTION	21040-510-TYP-20028	TYPICAL OPEN CUT / BORE	4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.	PIPELINE ROUTE	PERMANENT ROW	APPROVAL		COMPANY		UNIVERSAL PEGASUS INTERNATIONAL		FLORIDA SOUTHEAST CONNECTION		
PIPE ASSEMBLIES				PIPE COATING DATA				TYPICAL SADDLE BAG WEIGHTS		SPECIAL NOTES		LEGEND		APPROVALS								
PIPE COATING: 14 MIL MINIMUM FBE AND 24 MIL MINIMUM ARO				GIRTH WELD COATING: 2 PART EPOXY				INTERNAL COATING (YES/NO): NO				SPECIAL NOTES		LEGEND		APPROVALS						
GIRTH WELD COATING: 2 PART EPOXY				INTERNAL COATING (YES/NO): NO				TYPICAL PIPELINE MARKER ASSEMBLY		SPECIAL NOTES		LEGEND		APPROVALS								
INTERNAL COATING (YES/NO): NO				TYPICAL PIPELINE MARKER ASSEMBLY				PIPELINE MARKER "WARNING" DECAL		SPECIAL NOTES		LEGEND		APPROVALS								