

- water from crawl space pumps;
- footing drains;
- lawn watering;
- individual residential car washing;
- flows from riparian habitats and wetlands;
- swimming pool discharges;
- street wash water; and
- flows from fire fighting activities.

For existing permittees, the program shall, at a minimum, implement the requirements shown in Table 4.2.3(a) below and include descriptions of how they are implemented in the SWMP:

Table 4.2.3(a) Illicit Discharge Detection and Elimination – Best Management Practices (Existing Permittees)

BMPs	Measurable Goals
1. Legal Authority	1.a. Evaluate, and if necessary, modify the existing ordinance. If the ordinance is revised during the reporting period, submit a copy of the adopted ordinance with the annual report.
2. Outfall Map and Inventory	2.a. Maintain an updated map and an inventory showing the location of all outfalls from the MS4 and the names and locations of all waters of the State that receive discharges from those outfalls. The map and inventory must be submitted with each annual report. 2.b. Provide the number of outfalls added during the reporting period and the total number of outfalls in each annual report.
3. IDDE Plan	3. Implement the IDDE Plan below, following procedures described in the SWMP, to detect and address non-stormwater discharges to the MS4. The components of the IDDE Plan are as follows: 3.a. Conduct dry weather screening (DWS) inspections on 100% of the total outfalls within the 5-year permit term or use an alternate method approved by EPD. At a minimum, the permittee must conduct DWS inspections on 5% of the outfalls annually, or if the inspections are done by a geographical area, then one area or sector must be inspected each year, so that inspections are performed during each reporting period. If the permittee