	REVISIONS
$_{ m DATE}$:	DESCRIPTION:
02/24/2023	REVISIONS PER COUNTY COMMENTS
03/30/2023	REVISIONS PER COUNTY COMMENTS
06/12/2023	REVISIONS PER COUNTY COMMENTS
07/05/2023	REVISIONS PER GDOT COMMENTS
07/14/2023	REVISIONS PER GDOT COMMENTS
© COPYRIGHT 2022 THIS DRAWING IS T	© COPYRIGHT 2022 THIS DRAWING IS THE PROPERTY OF INNOVATE ENGINEERING & SURVEYING,
LLC. AND MA	LLC. AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.
OFFICE	DOCTIVENIES OF PITE 10 PECODE MANY DE CORTED BITT NOT ATTERED

N	Engin	PHONE:22 2214 N. Pat
willing	ORG EGISTERED No. 22564 ROFESSIONA	

AM D.
LEVEL II CERT. 8
DATE:
09/14/2022
DRAWN BY:
M. WILSON

CHECKED BY: B. KENT

 $34 \, \mathrm{or} \, 47$

PROJECT NUMBER 1669

ES&PC CHECKLIST

March Control Contro	Name & email of person filling out checklist: BILL KENT / bkent@innovatees.com	
The contract contract of the contract of the description of production of the contract of th	Plan Included	
Set operations and the first and content plants of the section of	Page # Y/N	*
Contractive Cont		
Section of the control of the cont		
Septiment of the content medicination of a decision of the content of the conte		
The content of the Selection content for the Content of the Selection of the Content of the Selection of the Content of the Selection of Selection		
Security of the security of	31 Y 3 The name and phone number of the 24-hour contact responsible for erosion, sedimentation and pollution controls.	
Section of the content of the cont		
Security (Continued and the continued of security of the continued of section of the continued of		
desirable with a first and the distribution protects make the first indicate the resident of the protect make the first indicate the resident of the protect make the first indicate the resident of the protect make the first indicate the resident of the protect make the first indicate the resident of the protect make the protect		33 Description of analytical methods to be used to collect and analyze the samples from each location. *
Secretary of the control of the cont		33 Y 34 Appendix B rationale for NTU values at all outfall sampling points where applicable. *
All substance of the process of a control sign of the region of the large of the control of the region of the large of the control of the region of the large o	ALL Y 7 Initial date of the Plan and the dates of any revisions made to the Plan including the entity who requested the revisions.	33 Y 35 Delineate all sampling locations, perennial and intermittent streams and other water bodies into which storm water is
3 7 3 Provide risk forms control calculation control communication and included adjusted of specific positions of the program control control control position and control contr		discharged also provide a summary chart of the justification and analysis for the representative sampling as applicable. *
Strong by paymentance and extracted developed activities and contribution with the contribution of the c		
establish and shallow the shallow we shall be a process of the pro		
The College of Applications of Control of Control of College of		
Sea a setting or Petr IV rappe 24 of the present of the content		
12 Supply reductions of relative transmitted at gaster fairly specified as according to report of the company of the compa		ALL Y 37 Graphic scale and North arrow.
a comprehensive your critical is a diametry to critical results and comprehensive your model shall be added in the comprehensive for improvements and the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements are presented at the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements and the comprehensive for improvements are presented at the comprehensive for improvements are presented at the comprehensive for improvements are admitted at the	31 Y 12 Design professional's certification statement and signature that the permittee's ES&PC Plan provides for an appropriate	
sample) a state of Part VID 8.2 (p) page 37 of the series to approach it is approached. NA 10 cours not to description of the operation of Series and description of the company of Series and description of Series and Seri	and comprehensive system of BMPs and sampling to meet permit requirements as stated on Part IV page 20 of the permit. *	
4 Clasery near the attenuent test.** The congram orbital september of the production of the producti	31 Y 13 Design professional certification statement and signature that the permittee's ES&PC Plan provides for representative	Proposed Contours 1": 400' Centerline Profile
and set reset startings requirement, partners count of staffs, and and earthead reset in visible on a contraction of the PM NA Spage 26 of the partner. 31 V 15 Clearly rote to be atternated to PM report of the atternate to PM report of the atternated to PM report of the atternated to PM report of the atternated to PM report of the atternation of the atternated to PM report of the atternation and atternated to PM report of the atternated to PM report of the att	sampling as stated on Part IV.D.6.c.(3) page 37 of the permit as applicable. *	N/A 39 Use of alternative BMPs whose performance has been documented to be equivalent to or superior to conventional BMPs
NA Since you have reasonable Plant IV-AS page 26 of to grow! No interest to the conduction and in other conducted or him ab 25 or 50 hortundarized stream before a measured in the processor of the processo	32 Y 14 Clearly note the statement that "The design professional who prepared the ES&PC Plan is to inspect the installation of the	
Source Courty make the severed that Non-exceptable test all motte conducted within the 25 or 40 feet undestrood a country of the severed from the undestrood burbands and control test careginal to the counted model that is a measured from the undestrood burbands and control test careginal to conseque variations and plants.		
but is a research from the port of orabid registering or within 25 factor the consisterand and but in a measured from the Junification Determination Level during the principle of any but of the consisteration and interest the following the principle of any but of the consisteration and interest the following the principle of any but of the consisteration and interest the following the principle of any but of the distingtion of the proposal		
N/A 15 Provide a description of any buffer encoderance and indicate whether a suffer varieties to require the provider and the provider an		
N/A 2 Frovide a description of any bulber exceptaments and indicate whether a burber validance before a burber validance which and a Stev valent becade on and within 20 Section the subject to the burber of the section of the subject to the burber of the section of the subject to the validation and continue to the burber of the subject to the subject to the subject to the subject to the validation of create the subject to t	'	
17 Clearly note the element that "Amendmentorevistra to the ESSPC Plan which have a significant efection BMPs with a hydralic corponent must be earliered by the desking profession." 18 Clearly note element that "Mose metarials shall not be deskinged to waters of the Sible, except a authorized by a Section 404 permit." 19 Clearly note element that "The escape of sediment from the site water has shall not be deskinged to waters of the Sible, except a authorized by a Section 404 permit." 19 Clearly note element that "The escape of sediment from the site water has shall be prevented by the installation of erosion and sediment across prior to laid distancing acrivities." 20 Y 20 Clearly note statement for the site work of the Sible, except as authorized by a Section 404 permit. 21 Y 21 Clearly note statement for the set water because of sediment from the site water has a sediment across on a sediment across on a sediment across on the service of the sediment of the supposed distance and sediment across on the sediment of the supposed distance and sediment across on the sediment of the		
hydraulic component must be carrieded by the design processional.* 3 Y 18 Celesty note the destinant into "Most internation soul note debrated to waters of the Stee, except as submitted by a Section 494 permit." 3 Y 20 Celesty note abtement that "Most internation and additional process and addit		
3.1 V 16 Ceaty note the debinant hat "Valest methrials shall not be discharged to waters of the State, except as authorized by a Scient 404 permit." 3.1 V 19 Ceaty note Settment that The escape of sediment from the size shall be prevented by the issualation of erotion and sediment control measures and practices prof bland discharge activities." 3.1 V 20 Cearly note Settment that "The escape of sediment source." 3.2 Cearly note between that "The escape of sediment source." 3.3 V 21 Cearly note the settment at "Valest measures and practices profit bland discharges source and sediment control measures shall be implained from the seal sediment source." 3.3 V 21 Cearly note the settment "Any disturbed area left exposed for a period greater than 14 days shall be substituted with muttor or humanian sediment control measures shall be implained from the settment "Any disturbed area left exposed for a period greater than 14 days shall be substituted with muttor or not minimally associated as any portion of a Boot impaired Stream Segment will be used for hose areas of the attention to the permit include the completed Appendix 1 listing at the BMPs hat will be used for hose areas of the attention to the permit include the completed Appendix 1 listing at the BMPs hat will be used for hose areas of the attention to the permit include the completed Stream Segment will be used for hose areas of the attention to the permit included in the TMD. Implementation Plan Segment (identified in liem 22 above) at least sk months prior to settlement that seen inalized for the limpaired Stream Segment will be used for several process and sediment complete and the construction and the construction shill be probleted." 3.2 V 25 Decorption of the measures that will be installed during the construction process to control process any site-specific conditions or requirements included in the TMD. Implementation Plan Segment (identified in liem 22 above) at least sk months prior to settlement that Segment that the distriction of the measures		
completed 31 V 19 Clearly note statement that "The escape of sediment from the site shall be prevented by the installation of erosion and sediment control measures and practices from 1 land disturbing activities." 31 V 20 Clearly note statement that "Erosion control measures will be maintained at all times. If full implementation of the approved plan does not provide for effective erosion control, additional erosion and sediment cource." 32 Periodic annihilation of the sediment focus of the sediment cource. 33 V 21 Clearly note the statement "Any disturbed area let exposed for a period greater han 14 days shall be stabilized with mulch or temporary seeding." N/A 22 Any construction activity with discharges strim water into an impaired Steam Segment, or within 1 linear mile upstream of and within the same watershed as, any portion of a Blota impaired Steam Segment within the same watershed as, any portion of a Blota impaired Steam Segment (dentified in item 22 above) at least six months some of section plans of the segment of the segment of the segment of the segment seed of the segmen	31 Y 18 Clearly note the statement that "Waste materials shall not be discharged to waters of the State, except as authorized by a	
31 Y 19 Clearly note statement that "The escape of sedment from the ask shall be prevented by the installation of eroson and sedment control measures and practices prior to land disturbing advites." 32 V 20 Clearly note statement from "The scape of sedment from the sale shall be prevented to control or easures and practices prior to land disturbing advites." Iffull implementation of the approved Plan does not provide for effective erosion control reasures shall be implemented to control or teat the addiminations. 33 V 21 Clearly note the statement "Any disturbed area left exposed for a period greater than 14 days shall be stabilized with mutch or temporary seeding." 34 V 27 Clearly note the statement "Any disturbed area left exposed for a period greater than 14 days shall be stabilized with mutch or temporary seeding." 35 V 27 Any construction activity which discharges storm water in ball impaired Stream Segment, or within 1 linear mix upstand and which it is same watershed as, any portion of a Bobs impaired Stream Segment (or within 1 linear mix upstand period. Or the period. A writer justification explaining the decision to use equivalent controls when a sediment traps for each common drainage boaton. Sediment strange without excellent traps of the properties and which discharges in the Impaired Stream Segment in the Company of the Impaired Stream Segment (or within 1 linear mix upstand as to within discharges in the Impaired Stream Segment in the Company of the Impaired Stream Segment in	Section 404 permit *	
sediment control measures and practices price 1 sind deathing actives. 2 Clearly note statement that "Crossin control measures will be maintained at all sines. If full implementation of he approved Plan does not provide for effective decision control, additional erosion and sedimentation measures shall be implemented to control or result he sediment source." 3 I V 2 Clearly note the statement "Any disturbed area let exposed for a period greater han 14 days shall be subtilized with much or being control or the statement variety seeding." N/A 2 Any construction activity which discharges sbrm water in bain impaired Stream Segment or within 1 linear mile upstream of and which in the same watershed as, any portion of a Blobs impaired Stream Segment water in bain impaired Stream Segment in the sedment has been finalleed for the impaired Stream Segment of bail to the completed Appendix 1 listing all the BMPs that will be used for hose areas of the site which discharge by the limited end to make a provided of the site has been achieved. A written included in the Plan for each common drainage boation in which a sadiment basin is not provided. A written included in the Plan for each common drainage boation in which a sadiment basin is not provided. A written included in the Plan for each common drainage boation in which a sadiment basin is not provided. A written included in the Plan for each common drainage boation in which a sadiment basin is not provided. A written included in the Plan for each common drainage boation in which a sadiment basin is not provided. A written included in the Plan for each common drainage boation in which a sadiment basin is not provided. A written included in the Plan for each common drainage boation in which a sadiment basin is not provided. A written included in the Plan for each common drainage boation in which as adment basin is not provided. A written included in the Plan for each common drainage boation in which as adment basin is not provided. A written included in the Plan for ea	31 Y 19 Clearly note statement that "The escape of sediment from the site shall be prevented by the installation of erosion and	
Plan does not provide for effective erosion control, additional erosion and sediment control measures shall be implemented to control or treat the sediment source.* 31. Y 21 Clearly not be a statement."Any disturbed area let exposed for a period greater than 14 days shall be stabilized with much or temporary seeding.* N/A 22 Any construction activity which discharges strimwater into an impaired Stream Segment, or within 1 linear mile upstream of and which he same watershed as, any portion of a Bob impaired Stream Segment, or within 1 linear mile upstream of and which he same watershed as, any portion of a Bob impaired Stream Segment, or within 1 linear mile upstream achieved. A writing linear that the permit. Include the completed Appends. I staffing all the BMPs that will be used for those areas of the site which discharge is the impaired Stream Segment.* N/A 21 If a TMDL Implementation Plan to additional provided in the TMDL Implementation Plan. 32 Y 24 BMPs for concrete maker churse, heppers and the rear of the vehicles. Washout of the drum at the construction sets is prohibited.* 33 Y 26 Description of the measures that will be inselled during the construction process to control pollutants in storm water from the surface are not feasible, as writing institution expertising of the measures that will be inselled during the construction process to control pollutants in storm water from the surface are not feasible, as writing institution operations have been completed. * 33 Y 26 Description of practices to provide cover for building materials and building products on site. * ** Histing this checklist for a project that is less than 1 acre and not part of a common development.* ** Histing this checklist for a project that is less than 1 acre and not part of a common development.* ** Histing this checklist for a project that is less than 1 acre and not part of a common development.* ** Histing this checklist for a project that is less than 1 acre and not part of a common development.* ** Histing this	sediment control measures and practices prior to land disturbing activities."	
25-29 Y 48 The Instend of disturbance for each phase of construction. 27-29 Y 48 The Instended of disturbance for each phase of construction. 28-29 Y 48 The Instended of disturbance for each phase of construction. 39 Provide a minimum of 67 cubic yeards of seatment storage per acre drained using a temporary sediment busing in the submitted of and within the same watershord as, any portion of a Bibbi Impaired Stream Segment runst comply with Part III. C. of the permit. Include the completed Appendix 1 ising all the BMPs that will be used for those areas of the site which discharge to the Impaired Stream Segment 8 is not provided. A written justification as to why 67 cubic yeards of storage is not attenuable must sho be greatly in the same segment and all caculations used by the design professional to obtain the required departments included in the TMD Implementation Plan.* 31 Y 24 SMPs for concrete washdown of tools, concrete mixer chules, hoppers and the rear of the vehicles. Washout of the orange at the construction spile is prohibited.* 32 Y 26 Description of the measures that will draw water from the surface are not feasible, a written justification explaining this decision must be included in the Plan. 32 Y 27 Description of the measures that will draw water from the surface are not feasible, a written justification explaining this decision must be included in the Plan. 33 Y 27 Description of the measures that will draw water from the surface are not feasible, a written justification explaining this decision must be included in the Plan. 34 Provide Market and provide and provide cover for building materials and building products on site. 35 Provide MSMPs for the remediation of all periodeum spills and leaks. 36 Provide desided drawings for all structural practices. Specifications must, at a minimum, meet the guidelines set forth in the Manual for Erosion and Sediment Control in Georgia.		31 Y 47 Soil series for the project site and their delineation.
31 Y 21 Clearly note the statement "Any disturbed area left exposed for a period greater than 14 days shall be stabilized with mulch or temporary seeding." N/A 22 Any construction activity which discharges storm water into an impaired Stream Segment, or within 1 linear mile upstream of and within the same watershed as, any portion of a Bibbl Impaired Stream Segment or within 1 linear mile upstream of and within the same watershed as, any portion of a Bibbl Impaired Stream Segment or within 1 linear mile upstream of and within the same watershed as, any portion of a Bibbl Impaired Stream Segment." (a of the permit, Include the completed Appendix 1 Ising all the BMPs that will be used for those areas of the size which discharge is the Impaired Stream Segment. N/A 23 If a TMDL Implementation Plan for sedimenthas been finalized for the Impaired Stream Segment of above) at least its months prior to submitted of MOI, the ESSPO Plan must address any site-specific conditions or requirements included in the TMDL Implementation Plan. ** 322 Y 24 BMPs for concrete washdown of bods, concrete mixer churse, hoppers and the rear of the vehicles. Washout of the drum at the construction site is prohibited. ** 333 Y 25 Provide BMPs bit the remediation of all petroleum spills and leaks. 344 Provide a minimum of 67 cubic yards of sediment traps for each common drainage location. Sediment storage volume must be in place prior to and during all land disturbance activities until rine stabilization of the six has been activated by the same propried of the design provisional to be design provisional to be design provisional to behalm the required sediment storage when using equivalent controls. When discharging from sediment basins not attainable must be included for structural BMPs and all cabulations used by the design provisional to behalm the required sediment storage when using equivalent controls. When discharging from sediment basins and implementation of the stable and water from the surface, unless inleasable. If outlet s		
or temporary seeding.* IN/A 22 Any construction activity which discharges storm water into an Impaired Steam Segment, or within 1 linear mile upstream of and within the same watershed as, any portion of a Biota Impaired Stream Segment must comply with Part III. C. of the permit. Include the completed Appendix 1 lising all the BMPs that will be used for those areas of the sile which discharge to the Impaired Stream Segment.* IN/A 23 If a TMDL Implementation Plan for sedimenthals been inalized for the Impaired Stream Segment (identified in item 22 above) at least six monits prior to submitted of NoII, the ESBPC Plan must address any site-specific conditions or requirements included in the TMDL Implementation Plan. * 32 Y 24 BMPs for concrete washdown of botos, concrete mixer chutes, hoppers and the rear of the vehicles. Washout of the drum at the construction perations list is prohibited. * 33 Y 25 Provide BMPs for the remediation of all perfoleum spills and building products on site. * 34 Provide and a lacitation in the TMDL Implementation Plan. * 25-29 Y 50 Location of Best Management Practices that are consistent with and no less stringent than the Manual br. Erosion and Sediment Control in Georgia. Use uniform coding symbols from the Manual Chapter 6, with legend. 35 Y 26 Description of the measures that will be installed during the construction process b control pollutants in storm water that will occur after construction operations have been completed. * 36 Provide dealed drawings for all structural practices. Include species, planting dates and sulfile propriate geographic region of Georgia. 37 Provide dealed drawings for all structural practices by provide cover for building materials and building products on site. * 38 Provide segetate plan, noting all territy and course and not part of a common development.		
N/A 22 Any construction activity which discharges storm water into an Impaired Stream Segment, or within 1 linear mile upstream of and within the same watershed as, any portion of a Bibbi Impaired Stream Segment must comply with Part III. C. of the permit. Include the completed Appendix 1 listing all fine BMPs that will be used for those areas of the site which discharge to the Impaired Stream Segment and the site which discharge to the Impaired Stream Segment that been finalized for the Impaired Stream Segment (dentified in item 22 all far TMDL Implementation Plan for sections that site included in the Plan for seat common drainage location in which a sediment basin is not attainable must also be given. Workshees from the Manual must be included for structural BMPs and all calculations used by the design professional to obtain the required sediment storage when using equivalent controls. When discharging from sediment basins and impoundment, permittees are required to utilize outlet structures that withdraw water from the surface are not leasable, a written justification explaining this decision must be included in the Plan. 23.2 Y 24 BMPs for concrete washdown of bots, concrete maker chules, hoppers and the rear of the vehicles. Washout of the drum at the constructions the is prohibited. * 25.29 Y 50 Location of Best Management Practices that are consistent with and no less stringent than the Manual for Erosion and Sedment Control in Georgia. Use uniform coding symbols from the Manual, Chapter 6, with legend. 25.29 Y 50 Provide deliated drawings for all structural practices. Specifications must at a minimum, meet the guidelines set forth in the Manual for Erosion and Sedment Control in Georgia. 25.29 Provide vegetative plan, noting all terrors and submitted or the appropriate geographic region of Georgia. 26. Provide vegetative plan, noting all terrors and muching rate of the appropriate geographic region of Georgia. 27. Provide vegetative plan, noting all terrors. Vegetative plan, noting all terrors. V		
of and within the same watershed as, any portion of a Biotal Impaired Stream Segment must comply with Part IIII. C. of the permit. Include the completed Appendix 1 listing all the BMPs that will be used for those areas of the site which discharge be the Impaired Stream Segment 1 so the Impaired Stream Segment 2 stream Segment 2 stream Segment 3 If a TMDL Implementation Plan for sediment has been finalized for the Impaired Stream Segment 1 solve) at least is more plan for sediment has been finalized for the Impaired Stream Segment 1 solve) at least is more plan for sediment has been finalized for the Impaired Stream Segment 1 solve) at least is more plan for sediment basis as not plan in the required Sediment basis is not provided. A written justification as b why 67 cubic yards of storage is not attainable must also be given. Worksheets from the Manual must be included in the Plan for each common drainage location in which a sediment basis is not provided. A written justification as b why 67 cubic yards of storage is not attainable must also be given. Worksheets from the Manual must be included in the Plan for each common drainage location in which a sediment basis is not provided. A written justification as b why 67 cubic yards of storage is not attainable must also be given. Worksheets from the Manual must be included in the Plan for each common drainage location in which a sediment basis is not provided. A written justification as b why 67 cubic yards of storage is not attainable must also be given. Worksheets from the Manual instituted of the provide water from the Surfacion as b why 67 cubic yards of storage is not attainable must also be given. Worksheets from the Manual instituted in the Plan for cubic and interpretation as the session must an attain the Manual of Plan for the uniform sediment basis and interpretation as the form the surface are not feasible, a written justification explaining this decision must and must be included in the Plan for the surface are not feasible. If outstanting the decisio		volume must be in place prior to and during all land disturbance activities until final stabilization of the site has been
justification as b why 67 cubic yards of strage is not attainable must also be given. Worksheets from the Manual must be included for structural BMPs and all calculations used by the design professional to obtain the required sediment storage when using equivalent controls. When discharging from sediment basins and impoundments, permittees are required to above) at least six months prior be submittal of NOI, the ES&PC Plan must address any site-specific conditions or requirements included in the TMDL Implementation Plan. * 32 Y 24 BMPs for concrete washdown of bols, concrete mixer chules, hoppers and the rear of the vehicles. Washout of the drum at the construction site is prohibited. * 33 Y 25 Provide BMPs for the remediation of all pervoleum spills and leaks. 34 Y 26 Description of the measures that will be installed during the construction operations have been completed. * 35 Y 27 Description of practices to provide cover for building materials and building products on site. * 36 Y 27 Description of practices to provide cover for building materials and building products on site. * 37 Y 28 Description of practices to provide cover for building materials and building products on site. * 38 Y 27 Description of practices to provide cover for building materials and building products on site. * 39 Y 27 Description of practices to provide cover for building materials and building products on site. * 30 Y 27 Description of practices to provide cover for building materials and building products on site. * 30 Y 27 Description of practices to provide cover for building materials and building products on site. * 31 If using this checklist for a project that is less than 1 acre and not part of a common development.		
included for structural BMPs and all calculations used by the design professional to obtain the required sediment storage when using equivalent controls. When discharging from sediment basins and impoundments, permittles are required to above) at least six months prior to submittal of NOI, the ES8PC Plan must address any site-specific conditions or requirements included in the TMDL Implementation Plan. * 24 BMPs for concrete washdown of bols, concrete mixer chules, hoppers and the rear of the vehicles. Washout of the drum at the construction site is prohibited. * 33 Y 25 Provide BMPs for the remediation of all petroleum spills and leaks. 34 Y 26 Description of the measures that will be installed during the construction process to control pollutants in storm water that will correct after construction operations have been completed. * 35 Provide vegetative plan, noting all temporary and permanent vegetative plan shall be site specific for appropriate time of year that seeding will take place and for the appropriate geographic region of Georgia. 36 If a TMDL Implementation Plan for sediment basins and impoundments, permittless are required to utilize outlet structures that withdraw water from the surface, unless infeasible. If outlet structures that will be design professional to obtain the required sediment storage when using equivalent controls. When discharging from sediment basins and impoundments, permittless are required to utilize outlet structures that withdraw water from the surface, unless intensible. If outlet structures that withdraw water from the surface, unless intensible, a written justification explaining this decision must be induced in the Plan. 36 Location of Best Management Practices that are consistent with and no less stringent than the Manual for Ecosion and Sediment Control in Georgia. Use uniform coding symbols from the Manual, Chapter 6, with legend. 37 Provide detailed drawings for all structural practices. Specifications must, at a minimum, meet the guidelines set forth in the M		· · · · · · · · · · · · · · · · · · ·
above) at least six months prior to submittal of NOI, the ES&PC Plan must address any site-specific conditions or requirements included in the TMDL Implementation Plan. * 25-29 Y 24 BMPs for concrete washdown of bols, concrete mixer chules, hoppers and the rear of the vehicles. Washout of the drum at the construction site is prohibited. * 25-29 Y 50 Location of Best Management Practices that are consistent with and no less stringent than the Manual for Erosion and Sediment Control in Georgia. Use uniform coding symbols from the Manual, Chapter 6, with legend. 25-29 Y 50 Location of Best Management Practices that are consistent with and no less stringent than the Manual for Erosion and Sediment Control in Georgia. Use uniform coding symbols from the Manual, Chapter 6, with legend. 25-29 Y 50 Location of Best Management Practices that are consistent with and no less stringent than the Manual for Erosion and Sediment Control in Georgia. 25 Provide detailed drawings for all structural practices. Specifications must, at a minimum, meet the guidelines set forth in the Manual for Erosion and Sediment Control in Georgia. 27 Description of practices to provide cover for building materials and building products on site. * 27 Description of practices to provide cover for building materials and building products on site. * 28 If using this checklist for a project that is less than 1 acre and not part of a common development.	to the Impaired Stream Segment. *	
requirements included in the TMDL Implementation Plan. * the surface are not feasible, a written justification explaining this decision must be included in the Plan. 32 Y 24 BMPs for concrete washdown of bols, concrete mixer chutes, hoppers and the rear of the vehicles. Washout of the drum at the construction site is prohibited. * 25-29 Y 50 Location of Best Management Practices that are consistent with and no less stringent than the Manual for Erosion and Sediment Control in Georgia. Use uniform coding symbols from the Manual, Chapter 6, with legend. 33 Y 26 Description of the measures that will be installed during the construction process to control pollutants in storm water that will occur after construction operations have been completed. * 33 Y 27 Description of practices to provide cover for building materials and building products on site. * 34 If using this checklist for a project that is less than 1 acre and not part of a common development. 35 If using this checklist for a project that is less than 1 acre and not part of a common development.		when using equivalent controls. When discharging from sediment basins and impoundments, permittees are required to
32 Y 24 BMPs for concrete washdown of bols, concrete mixer chules, hoppers and the rear of the vehicles. Washout of the drum at the construction site is prohibited. * Sediment Control in Georgia. Use uniform coding symbols from the Manual, Chapter 6, with legend. 33 Y 25 Provide BMPs for the remediation of all petroleum spills and leaks. 30 Y 51 Provide detailed drawings for all structural practices. Specifications must, at a minimum, meet the guidelines set forth in the Manual for Erosion and Sediment Control in Georgia. 33 Y 26 Description of the measures that will be installed during the construction process to control pollutants in storm water that will occur after construction operations have been completed. * 30 Y 52 Provide vegetative plan, noting all temporary and permanent vegetative practices. Include species, planting dates and seeding, fertilizer, lime and mulching rates. Vegetative plan shall be site specific for appropriate geographic region of Georgia. * If using this checklist for a project that is less than 1 acre and not part of a common development		,
at the construction site is prohibited. * Sediment Control in Georgia. Use uniform coding symbols from the Manual, Chapter 6, with legend. 33 Y 25 Provide BMPs for the remediation of all petroleum spills and leaks. Y 26 Description of the measures that will be installed during the construction process to control pollutants in storm water that will occur after construction operations have been completed. * 30 Y 51 Provide detailed drawings for all structural practices. Specifications must, at a minimum, meet the guidelines set forth in the Manual for Erosion and Sediment Control in Georgia. Will occur after construction operations have been completed. * 30 Y 52 Provide vegetative plan, noting all temporary and permanent vegetative practices. Include species, planting dates and seeding, fertilizer, lime and mulching rates. Vegetative plan shall be site specific for appropriate time of year that seeding will take place and for the appropriate geographic region of Georgia. * If using this checklist for a project that is less than 1 acre and not part of a common development		
25 Provide BMPs for the remediation of all petroleum spills and leaks. 30 Y 51 Provide detailed drawings for all structural practices. Specifications must, at a minimum, meet the guidelines set forth in the Manual for Erosion and Sediment Control in Georgia. will occur after construction operations have been completed. * 27 Description of practices to provide cover for building materials and building products on site. * 30 Y 51 Provide detailed drawings for all structural practices. Specifications must, at a minimum, meet the guidelines set forth in the Manual for Erosion and Sediment Control in Georgia. 30 Y 52 Provide vegetative plan, noting all temporary and permanent vegetative practices. Include species, planting dates and seeding, fertilizer, lime and mulching rates. Vegetative plan shall be site specific for appropriate time of year that seeding will take place and for the appropriate geographic region of Georgia. * If using this checklist for a project that is less than 1 acre and not part of a common development		
The Manual for Erosion and Sediment Control in Georgia. Will occur after construction operations have been completed. * 27 Description of practices to provide cover for building materials and building products on site. * 28 Description of practices to provide cover for building materials and building products on site. * 29 Description of practices to provide cover for building materials and building products on site. * 29 Provide vegetative plan, noting all temporary and permanent vegetative practices. Include species, planting dates and seeding, fertilizer, lime and mulching rates. Vegetative plan shall be site specific for appropriate time of year that seeding will take place and for the appropriate geographic region of Georgia. * If using this checklist for a project that is less than 1 acre and not part of a common development.		
will occur after construction operations have been completed. * 27 Description of practices to provide cover for building materials and building products on site. * 30 Y 52 Provide vegetative plan, noting all temporary and permanent vegetative practices. Include species, planting dates and seeding, fertilizer, lime and mulching rates. Vegetative plan shall be site specific for appropriate time of year that seeding will take place and for the appropriate geographic region of Georgia. * If using this checklist for a project that is less than 1 acre and not part of a common development		
seeding, fertilizer, lime and mulching rates. Vegetative plan shall be site specific for appropriate time of year that seeding will take place and for the appropriate geographic region of Georgia. * If using this checklist for a project that is less than 1 acre and not part of a common development		
will take place and for the appropriate geographic region of Georgia. * If using this checklist for a project that is less than 1 acre and not part of a common development		
		will take place and for the appropriate geographic region of Georgia.
L.		* If using this checklist for a project that is less than 1 acre and not part of a common development but within 200 ft of a perennial stream, the * checklist items would be N/A

but within 200 ft of a perennial stream, the * checklist items would be N/A.

Effective January 1, 2022

EROSION, SEDIMENTATION & POLLUTION CONTROL PLAN CHECKLIST

Date on Plans:

BRIGGSTON ROAD